


# LICENCE

**No. 20585**

Issued to:  
Applicant:  
**R-Tech**  
**Rue de Mons, 3**  
**4000 LIEGE**  
**Belgium**

Licensee:  
**Schreder S.A.**  
**Rue de Lusambo, 67**  
**1190 BRUXELLES**  
**Belgium**



Product : road, square, street, flood lighting  
Trade name(s) : SCHREDER  
Type(s)/model(s) : OMNIFLOOD 1, OMNIFLOOD 2, OMNIFLOOD 3

The product and any acceptable variation thereto is specified in the annex to this licence and the documents therein referred to.


SGS CEBEC hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard specified in annex
- an inspection of the production location
- a certification agreement with the number 1173

SGS CEBEC hereby grants the right to use the CEBEC certification mark

The ENEC/CEBEC certification mark may be applied to the product as specified in this licence for the duration of the ENEC/CEBEC certification agreement and under the conditions of the ENEC/CEBEC certification agreement.

This licence is issued on: 06/12/2017



ir. C. Lana,  
Certification Manager

© Only integral publication of this certificate, including the annex, is allowed

This certificate is only valid combined with the publication on the following web address: [www.sgs.com/ee](http://www.sgs.com/ee)



## SPECIFICATION OF THE CERTIFIED PRODUCT

### Product data

Product	:	road, square, street, flood lighting
Trade name(s)	:	SCHREDER
Type(s)/Model(s)	:	OMNIFLOOD 1, OMNIFLOOD 2, OMNIFLOOD 3
description	:	Flood and tunnel lighting
rated voltage (Un)	:	120-240 V
nature of supply	:	ac
rated frequency	:	50-60 Hz
rated current (In)	:	350-500-700-1000 mA
class	:	class I
degree of protection	:	IP66
additional information	:	IK10

### Product data - type OMNIFLOOD 1

lamp(s)	:	8-16-24 LED's
rated ambient temperature (ta)	:	Ta 50°C
rated power	:	9 up to 72 W

### Product data - type OMNIFLOOD 2

lamp(s)	:	32-48 LED's
rated ambient temperature (ta)	:	Ta 40-50°C
rated power	:	35 up to 149 W

### Product data - type OMNIFLOOD 3

lamp(s)	:	72 LED's
rated ambient temperature (ta)	:	Ta 40-50°C
rated power	:	79 up to 224 W

## TESTS

### Test requirements

EN 60598-1:2015  
 EN 60598-2-3:2003 + A1:2011  
 EN 60598-2-5:2015



### Test results

The test results are laid down in certification file 628807/01.

### Remarks

This certificate is based on test reports Nos. P3528-32-I and P3528-32-Ia.


### Conclusion

The examination proved that all test requirements were met.

Checked by, project leader : Christian Maes - 06/12/2017

Department Manager,  
Product Certification :

Certification Manager :

 2017-12-06

## FACTORY LOCATION(S)

Schröder do Brasil Iluminação Ltda.  
Rua Iracema Lucas, 415  
Distrito Industrial Vinhedo  
13280-000 SAO PAULO  
Brazil

Schreder TOV  
Vul. Mykulynetska 46B  
46000 TERNOPIL  
Ukraine

Schreder (China) Lighting Industrial Co., Ltd  
No.40 Xinye 2 Street, Tianjin Economic Technological Development Zone West Zone,  
300462 Tianjin City, P.R.China  
China

Socolec S.A.  
Av. de Roanne, 66  
Poligono Industrial "EL HENARES"  
19180 MARCHAMALO (GUADALAJARA)  
Spain

Schröder Iluminação S.A.  
Rua da Fraternidade Operária, n° 3  
2795-491 CARNAXIDE, OEIRAS  
Portugal

Comatelec S.A.  
Z.I.  
18400 SAINT FLORENT S/CHER  
France

Tungsram-Schröder Világítási Berendezések Zrt  
Tópart 2  
2084 PILISSZENTIVAN  
Hungary